

VIJAYANAGARA SRI KRISHNADEVARAYA UNIVERSITY, BELLARY.
[ENGINEERING DEPARTMENT]



NO. VSKUB/ENGG/Quo/G R W /2026-27/ 310

Date: 6 -07-2026

QUOTATION

Sealed quotations subscribing the name Air Conditioners Repairs and General Repairs Works in Naveli Girls Hostel, Science Faculty Building In The Premises of Vijayanagara Sri Krishnadevaraya University, Jnana Sagara Campus, Ballari. So as to reach this office on or before 13 .07.2026 and quotation should be addressed to Registrar, V.S.K. University, Vinayaknagar, Cantonment, Ballari.

NAME OF WORK:-AIR CONDITIONERS REPAIRS AND GENERAL REPAIRS WORKS IN NAVELI GIRLS HOSTEL,SCIENCE FACULTY BUIDLING IN THE PREMISES OF VIJAYANAGARA SRI KRISHNADEVARAYA UNIVERSITY, BALLARI.

Sl. No	Name of materials / Items or Work	Unit	Quantity	Rate quoted per unit	
				In figures	In words
1	Supplying & filling refrigerant (F-22/F/12) for air conditioning equipment's. Which includes the labour & Nitrogen gas for pressure and leak testing	Kg	12.00		
2	Supply and fixing of 3 pole power contactor with NO/NC contacts on existing wood/panel board using necessary bolts, nuts, washers and wiring etc., complete with AC-3 Rating and as per IS-13947.	Each	1.00		
3	Supplying and fixing capacitor's (of approved make) for window /split air conditioners.	Each	1.00		
4	Supplying and installation of insulated refrigerant copper tubing of 5/8" and 3/8" with polythene foam insulation 3 core 80 stand copper wiring between indoor and outdoor unit Leak testing oil and gas charging for additional piping length of tube	Mtr	6.00		
5	Installation charges for split type air conditioner with allied works for one indoor and one outdoor unit is to be mounted on suitable Angle Iron support up to 3.0 Ton split/cassette type A/C.	Each	2.00		
6	Providing and fixing flush door shutter made out of solid core block board type, well seasoned , chemically treated hard wood battens and internal frame with minimum 45 mm wide wooden frame around door shutters covered with cross bonded wooden sheets (core veneer) hot pressed and fastened on both sides of the door using liquid phenol formaldehyde resin as per IS specifications 2202 (part-I) 1991. from manufacturer complete as per specification. do-30 mm thick both side commercial	M ²	1.76		
6A	Providing and fixing chromium plated brass butt hinges with necessary chromium plated brass screws etc. complete.: 75x40x2.5 mm (ordinary type))	Each	17.00		
6B	Providing and fixing bright finished brass tower bolts (barrel type) with necessary screws etc.100x10mm (PWD , S.R 2023-24, Volume-2, Item Sl No 12.76.4 , page No.107)	Each	17.00		
6C	Providing and fixing door latch with necessary screws Bright finished brass latch	Each	9.00		
6D	Providing and fixing bright finished brass handles with screws etc Brass handles 75 mm with plate 125x32 mm	Each	4.00		

7	SS Door stopper 75mm	Nos	9.00		
8.	Providing & fixing 30mm thick factory made rigid foam Prelam Panelled Door Shutters made from M.S. tube of 19x19mm, 19 gauge for stiles and 15x15mm for top & bottom rails, covered with heat moulded Prelaminated PVC C Channel of 5mm thick sheet & 30x50mm wide to form stiles & 5mm thick & 75mm wide Prelaminated PVC Sheets for top rail, lock rail & bottom rail on either side & 5mm thick, 20mm wide cross PVC sheet as gap insert for top rail & bottom rail, Panelling of 5mm thick PVC sheet Prelaminated on either side fitted in the M.S. frame, Sealed to the stiles & rails with PVC Designer beading on either side & joined together with solvent cement adhesive etc., Complete as per manufacturers specification & direction of Engineer-in-charge fixed to frames with 3 nos of 75mm Aluminium hinges.	M ²	1.47		
9.	Providing & fixing of 2.5 track x 2-panel sliding windows made out of multi chambered UPVC(Matching to RAL-9016) sections and with minimum TiO ₂ (Titanium Dioxide) at 6PHR with TPE(Thermo Plastic Elastomer) and lead free, gaskets -grey colour having isolated drainage and reinforced with Galvanized Iron profile through-out the window frame. The outer frame having an overall size of 94mm width x 45mm height with reinforcement of 1mm thickness and Sash with overall size of 39mm x 58mm with GI reinforcement of 1.5mm and mesh sash of size 25mm x 42mm. Coextruded Glazing bead for fixing of glass shall be of size 20mm x 24 mm. Windows shall be provided with 5mm plain float glass, standard hardware & single point locking system with touch lock. Wall thickness of frame & sash shall be of 2mm-2.5mm. Maximum possible size – 1819mm x 1819mm. (The cost is inclusive of all fixtures and separate charges for minor T&P's shall not be made)	M ²	5.40		
	GST Extra				

I have read the terms and conditions for the above work and I shall abide by the same.

Roknab

REGISTRAR
V.S.K. UNIVERSITY,
BALLARI-583105.

K. Dyk

ans

TERMS & CONDITIONS:

1. The rates quoted should be excluding GST .
2. The right to reject the quotation is vested with University authorities.
3. The quoted rates should be valid at least for 03 months.
4. The rate quoted should be exclusive of GST , transportation, loading & unloading charges etc. complete.

Copy:

- 1) The Director , ICT Department, VSK University, Ballari-583105 for necessary action to upload the quotation in university website for 07 days or up to last date.
- 2) Notice Board.